



Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

SECTION 1. IDENTIFICATION

Product name : CYCLO BATTERY PROT AERO 12/11 OZ

Product code : C121

Manufacture or supplier's details

Company Name of Supplier : Niteo Products, LLC

Address : 720 Vaiden Dr, Hernando, MS 38632

Email : EHS@niteoproducts.com

Phone Number : +1 (844) 696-4836

Australian Importer : Cyclo Chemicals Australia

Address : 2/19 Technology Circuit Hallam 3803

Email : sales@cycloaustralia.com

Phone Number : +61 3 9702 4314

Website : www.cycloaustralia.com.au

Poison Information : Ph 13 11 26

Recommended use of the chemical and restrictions on use

Recommended use : PROTECTANT

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 3 (Central nervous system)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Neurologic: other (neuropsychological effects, audi-

tory dysfunction and effects on color vision))

Aspiration hazard : Category 1

GHS label elements

CYCLO® BATTERY PROTECTOR



Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

Hazard pictograms







Signal word : Danger

Hazard statements : Extremely flammable aerosol.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Suspected of damaging the unborn child.

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision))

through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.





Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Petrolatum	8009-03-8	>= 20 - < 30
Distillates (petroleum)	64742-47-8	>= 20 - < 30
Propane	74-98-6	>= 10 - < 20
Butane	106-97-8	>= 10 - < 20
Toluene	108-88-3	>= 10 - < 20
Solvent naphtha (petroleum)	64742-89-8	>= 5 - < 10

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on clothes, remove clothes.

Remove contaminated clothing. If irritation develops, get med-

ical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

CYCLO® BATTERY PROTECTOR



Version 2.3

Revision Date: 04/10/2024

SDS Number: 600000001216

Date of last issue: 04/09/2024 Date of first issue: 09/30/2017

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this

material.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- :

ucts

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Remove all sources of ignition. Ensure adequate ventilation.

Avoid breathing dust.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.





Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Use only explosion-proof equipment.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Petrolatum	8009-03-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm	OSHA P0

CYCLO® BATTERY PROTECTOR



Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

			1,800 mg/m3	
Butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
Solvent naphtha (petroleum)	64742-89-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.





Version **Revision Date:** Date of last issue: 04/09/2024 SDS Number: 04/10/2024 60000001216 Date of first issue: 09/30/2017 2.3

In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection

Remarks Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Flame-resistant clothing

Safety shoes

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not smoke. When using do not eat or drink.



Appearance aerosol

Colour not determined

Odour hydrocarbon-like

Odour Threshold not determined

рН not determined

Melting point/freezing point not determined

Boiling point/boiling range not determined

-104.45 °C Flash point

> Method: closed cup Value for Component

Evaporation rate not determined

Flammability (solid, gas) not determined

Self-ignition not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

0.7 %(V) not determined





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/09/2024

 2.3
 04/10/2024
 600000001216
 Date of first issue: 09/30/2017

Vapour pressure : No data available

Relative vapour density : not determined

Density : not determined

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

not determined

Decomposition temperature : not determined

Viscosity

Viscosity, kinematic : not determined

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability: No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

Carbon oxides

SECTION 11.TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

CYCLO® BATTERY PROTECTOR



Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

Components:

Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Remarks: Information given is based on data obtained from

similar substances.

Distillates (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.28 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Butane:

Acute oral toxicity : LD50 (Rat): > 5 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 3.16 g/kg

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, males): 25.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

Solvent naphtha (petroleum):

Acute oral toxicity : LD50 (Rat): > 8,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 7,630 mg/m3

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rat): > 4,000 mg/kg





Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Petrolatum:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Remarks: Information given is based on data obtained from similar substances.

Distillates (petroleum):

Result: Possibly irritating to skin

Butane:

Result: Possibly irritating to skin

Toluene:

Result: Irritating to skin.

Solvent naphtha (petroleum):

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Petrolatum:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Remarks: Information given is based on data obtained from similar substances.

Distillates (petroleum):

Result: Possibly irritating to eyes

Butane:

Result: Possibly irritating to eyes

CYCLO® BATTERY PROTECTOR



Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

Toluene:

Result: Irritating to eyes.

Solvent naphtha (petroleum):

Result: Possibly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Petrolatum:

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

Remarks: Information given is based on data obtained from similar substances.

Toluene:

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

Components:

Propane:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

CYCLO® BATTERY PROTECTOR



Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Toluene:

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

STOT -single exposure

May cause drowsiness or dizziness.

Components:

Toluene:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

Solvent naphtha (petroleum):

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT -repeated exposure

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

Components:

Toluene:

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects

on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Toluene:

May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum):

May be fatal if swallowed and enters airways.

CYCLO® BATTERY PROTECTOR



Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vom-

iting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14.TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Packing instruction (cargo : 203

aircraft)

Packing instruction : 203

(passenger aircraft)

IMDG-Code

UN number : UN 1950 Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no









Version Revision Date: SDS Number: Date of last issue: 04/09/2024 2.3 04/10/2024 600000001216 Date of first issue: 09/30/2017

Transport in bulk according to Annex II of MARPOL 73/78andthe IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1950 Proper shipping name : Aerosols

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 ERG Code : 126 Marine pollutant : no



SECTION 15. REGULATORY INFORMATION

EPCRA -Emergency Planning and Community Right-to-KnowAct

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Toluene	108-88-3	100	100 (F005)
Toluene	108-88-3	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312Hazards : Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Toluene 108-88-3 >= 10 - < 20 %

California Prop. 65

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.





Version 2.3

Revision Date: 04/10/2024


SDS Number: 60000001216

Date of last issue: 04/09/2024 Date of first issue: 09/30/2017

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard

Revision Date : 04/10/2028

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN