

SAFETY DATASHEET



CYCLO® MAX44DIESEL TF SYS CLNR W/DPF & EGR

Version	Revision Date:	SDS Number:	Date of last issue: 05/28/2024
2.7	04/23/2025	600000001105	Date of first issue: 09/27/2017

SECTION 1. IDENTIFICATION

Product name : CYCLO MAX44 DIESEL TFS CLN DPR&EGR 6/16OZ

Product code : C44D

Manufacture or supplier's details

Company Name of Supplier	: Niteo Products, LLC
Address	: 720 Vaiden Dr, Hernando, MS 38632
Email	: EHS@niteoproducts.com
Phone Number	: +1 (844) 696-4836
Australian Importer	: Cyclo Chemicals Australia
Address	: 2/19 Technology Circuit Hallam 3803
Email	: sales@cycloaustralia.com
Phone Number	: +61 3 9702 4314
Website	: www.cycloaustralia.com.au
Poison Information	: Ph 13 11 26

Recommended use of the chemical and restrictions on use

Recommended use : DIESEL FUEL TREATMENT

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	: Category 4
Acute toxicity (Inhalation)	: Category 4
Acute toxicity (Dermal)	: Category 4
Skin irritation	: Category 2
Carcinogenicity	: Category 2
Reproductive toxicity	: Category 1B
Specific target organ toxicity - single exposure	: Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure	: Category 2 (Liver, thymus, Bone marrow)
Aspiration hazard	: Category 1

GHS label elements

SAFETY DATASHEET



CYCLO® MAX44DIESEL TF SYS CLNR W/DPF & EGR

Version	Revision Date:	SDS Number:	Date of last issue: 05/28/2024
2.7	04/23/2025	600000001105	Date of first issue: 09/27/2017

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

Combustible liquid.
May be fatal if swallowed and enters airways.
Harmful in contact with skin or if inhaled.
Causes skin irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
May damage fertility or the unborn child.
May cause damage to organs (Liver, thymus, Bone marrow) through prolonged or repeated exposure.

Precautionary statements

:

Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTRE/ doctor.
IF ON SKIN: Wash with plenty of water. Call a POISON CENTRE/ doctor if you feel unwell.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/ doctor if you feel unwell.
IF exposed or concerned: Get medical advice/ attention.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

CYCLO® MAX44DIESEL TF SYS CLNR W/DPF & EGR

Version 2.7 Revision Date: 04/23/2025 SDS Number: 600000001105 Date of last issue: 05/28/2024
Date of first issue: 09/27/2017

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Diesel fuel no. 2	68476-34-6	$\geq 70 - < 90$
Kerosene	8008-20-6	$\geq 30 - < 50$
Solvent naphtha (petroleum)	64742-94-5	$\geq 5 - < 10$
Alkanes, C10-C20 branched and linear	928771-01-1	$\geq 1 - < 5$
2-Butoxyethanol	111-76-2	$\geq 1 - < 5$
Naphthalene	91-20-3	$\geq 1 - < 5$
Phenol, dodecyl- branched	210555-94-5	$\geq 0.1 - < 1$

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Harmful in contact with skin or if inhaled.
Causes skin irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
May damage fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.

**CYCLO® MAX44DIESEL TF SYS CLNR W/DPF
& EGR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/28/2024
2.7	04/23/2025	600000001105	Date of first issue: 09/27/2017

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.

CYCLO® MAX44DIESEL TF SYS CLNR W/DPF & EGR

Version 2.7 Revision Date: 04/23/2025 SDS Number: 600000001105 Date of last issue: 05/28/2024
Date of first issue: 09/27/2017

Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diesel fuel no. 2	68476-34-6	TWA (Inhalable fraction and vapor)	100 mg/m ³ (total hydrocarbons)	ACGIH
Kerosene	8008-20-6	TWA	100 mg/m ³	NIOSH REL
		TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
Solvent naphtha (petroleum)	64742-94-5	TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
2-Butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m ³	NIOSH REL
		TWA	50 ppm 240 mg/m ³	OSHA Z-1
		TWA	25 ppm 120 mg/m ³	OSHA P0
Naphthalene	91-20-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m ³	NIOSH REL
		ST	15 ppm	NIOSH REL

SAFETY DATASHEET


**CYCLO® MAX44DIESEL TF SYS CLNR W/DPF
& EGR**

Version 2.7 Revision Date: 04/23/2025 SDS Number: 600000001105 Date of last issue: 05/28/2024
Date of first issue: 09/27/2017

			75 mg/m3	
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
2-Butoxyethanol	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI

Personal protective equipment

Hand protection



Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles



Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.



Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : red

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : > 66 °C

Flash point : > 62 °C

SAFETY DATASHEET



CYCLO® MAX44DIESEL TF SYS CLNR W/DPF & EGR

Version 2.7	Revision Date: 04/23/2025	SDS Number: 600000001105	Date of last issue: 05/28/2024 Date of first issue: 09/27/2017
----------------	------------------------------	-----------------------------	---

Method: closed cup

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: 5 %(V)
Lower explosion limit / Lower flammability limit	: 0.7 %(V)
Vapour pressure	: 1 - 10 mmHg (37 °C)
Relative vapour density	: 4.5
Density	: 0.8546 g/cm3
Solubility(ies) Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity Viscosity, kinematic	: No data available
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents Not applicable
Hazardous decomposition products	: Carbon oxides

**CYCLO® MAX44DIESEL TF SYS CLNR W/DPF
& EGR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/28/2024
2.7	04/23/2025	600000001105	Date of first issue: 09/27/2017

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Harmful in contact with skin or if inhaled.

Product:

Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: 4.06 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: 1,781 mg/kg Method: Calculation method

Components:**Diesel fuel no. 2:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: LC50 (Rat, male and female): 4.1 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	: LD50 (Rabbit): > 4,300 mg/kg Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Kerosene:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 420
Acute inhalation toxicity	: LC50 (Rat): > 5.8 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**CYCLO® MAX44DIESEL TF SYS CLNR W/DPF
& EGR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/28/2024
2.7	04/23/2025	600000001105	Date of first issue: 09/27/2017

Solvent naphtha (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3,800 mg/m³
Exposure time: 4 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Alkanes, C10–C20 branched and linear:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

2-Butoxyethanol:

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Guinea pig): > 633 ppm
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg
Assessment: The component/mixture is moderately toxic after single contact with skin.

Naphthalene:

Acute oral toxicity : LD50 (Mouse, male): 533 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.4 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,500 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Phenol, dodecyl-branched:

Acute oral toxicity : LD50 (Rat): 2,100 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,000 mg/kg

**CYCLO® MAX44DIESEL TF SYS CLNR W/DPF
& EGR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/28/2024
2.7	04/23/2025	600000001105	Date of first issue: 09/27/2017

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:**Diesel fuel no. 2:**

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

Kerosene:

Result: Irritating to skin.

Solvent naphtha (petroleum):

Result: Mild skin irritation

2-Butoxyethanol:

Method: Directive 67/548/EEC, Annex V, B.4.

Result: Irritating to skin.

Naphthalene:

Result: Possibly irritating to skin

Phenol, dodecyl-branched:

Assessment: Causes burns.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**Diesel fuel no. 2:**

Species: Rabbit

Result: Possibly irritating to eyes

Method: OECD Test Guideline 405

Kerosene:

Result: Possibly irritating to eyes

Solvent naphtha (petroleum):

Result: Possibly irritating to eyes

**CYCLO® MAX44DIESEL TF SYS CLNR W/DPF
& EGR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/28/2024
2.7	04/23/2025	600000001105	Date of first issue: 09/27/2017

2-Butoxyethanol:

Result: Irritating to eyes.

Method: OECD Test Guideline 405

Naphthalene:

Result: Possibly irritating to eyes

Phenol, dodecyl-branched:

Assessment: Risk of serious damage to eyes.

Remarks: Causes eye burns.

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Diesel fuel no. 2:**

Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

2-Butoxyethanol:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

Components:**Diesel fuel no. 2:**

Genotoxicity in vitro	:	Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay) Result: positive
Genotoxicity in vivo	:	Test Type: In vivo micronucleus test Species: Mouse Result: negative

2-Butoxyethanol:

Genotoxicity in vitro	:	Test Type: Ames test Test system: Salmonella typhimurium
-----------------------	---	---

**CYCLO® MAX44DIESEL TF SYS CLNR W/DPF
& EGR**

Version 2.7	Revision Date: 04/23/2025	SDS Number: 600000001105	Date of last issue: 05/28/2024 Date of first issue: 09/27/2017
----------------	------------------------------	-----------------------------	---

Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:**Diesel fuel no. 2:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Naphthalene:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

IARC

Group 2B: Possibly carcinogenic to humans

Naphthalene 91-20-3

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Reasonably anticipated to be a human carcinogen

Naphthalene 91-20-3

Reproductive toxicity

May damage fertility or the unborn child.

Components:**Phenol, dodecyl-branched:**

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

STOT –single exposure

May cause drowsiness or dizziness.

Components:**Kerosene:**

Assessment: May cause drowsiness or dizziness.

STOT –repeated exposure

May cause damage to organs (Liver, thymus, Bone marrow) through prolonged or repeated exposure.

Components:**Diesel fuel no. 2:**

Target Organs: Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

SAFETY DATASHEET



CYCLO® MAX44DIESEL TF SYS CLNR W/DPF & EGR

Version	Revision Date:	SDS Number:	Date of last issue: 05/28/2024
2.7	04/23/2025	600000001105	Date of first issue: 09/27/2017

Target Organs: thymus

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: Bone marrow

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Diesel fuel no. 2:

May be fatal if swallowed and enters airways.

Kerosene:

May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum):

May be fatal if swallowed and enters airways.

Alkanes, C10–C20 branched and linear:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

**CYCLO® MAX44DIESEL TF SYS CLNR W/DPF
& EGR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/28/2024
2.7	04/23/2025	600000001105	Date of first issue: 09/27/2017

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations**IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA -Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Naphthalene	91-20-3	100	3820
Benzene	71-43-2	10	10 (D018)

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethylenediamine; 1,2-diaminoethane	107-15-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SAFETY DATASHEET



CYCLO® MAX44DIESEL TF SYS CLNR W/DPF & EGR

Version 2.7 Revision Date: 04/23/2025 SDS Number: 600000001105 Date of last issue: 05/28/2024
Date of first issue: 09/27/2017

Aspiration hazard
Skin corrosion or irritation

SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

2-Butoxyethanol	111-76-2	>= 1 - < 5 %
Naphthalene	91-20-3	>= 1 - < 5 %


California Prop. 65

WARNING: This product can expose you to chemicals including Naphthalene, Benzene, Formaldehyde, which is/are known to the State of California to cause cancer, and Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 04/23/2029

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN